fluid

Specifications:


- Metal construction
- → Pressure balancing volume control
- → Maximum temperature limit stop for added safety
- > Integral stop check valves for easy maintenance
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:


F1001T	Sleeve tube and cap
FP6016041	Quad Handle
FP6001033-1PB	Square Cover Plate
FP40120	3-Function Hand Shower*
FA803	Slide Bar with Integral Outlet
FP6001006	60" Shower Hose*

* Matte Black kits feature the FP6001007MB Shower Hose & FP40130MB 3-Function Hand Shower

Features:







Speed Connect

Quad 3-Function Hand Shower Trim Kit with FA802 Slide Bar

F161019T



Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)

fluid

Technical Drawing


F161019T














Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant EPA Watersense Listed (excluding MB Version)

Flow Rate:

Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower @ 1.5 gpm: **F161019T-15**