

Specifications:

- ➔ Metal construction
- ➔ Pressure balancing volume control with 2-way, two handle diverting
- ➔ Maximum temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- ➔ Requires the fluid F1012B or F1022B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Sleeve tube and cap
FP6016041	Quad Handle
FP801013	Diverter Sleeve
FP605752	Diverter Handle
FP601143-2PB	Square Cover Plate
FP40120	3-Function Hand Shower*
FA803	Slide Bar with Integral Outlet
FP6001006	60" Shower Hose*
FP6056034	Cubed Tub Spout

Kit with Alternate Handle: **F162074T-AS**



* Matte Black kits feature the FP6001007MB Shower Hose & FP40130MB 3-Function Hand Shower

Features:

Requires 2-way diverting F1012B or F1022B valve

Integral Stops Bubble Level

Speed Connect

Quad Tub & Hand Shower Trim Kit with FA803 Slide Bar


F162074T



Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)

Technical Drawing

F162074T



Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1

CSA B125.1

IAPMO / cUPC Listed

ADA Compliant

EPA Watersense Listed (excluding MB Version)

Flow Rate:

Showerhead 1.8 gpm @ 60 psig

Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Hand Shower
@ 1.5 gpm: **F162074T-15**