fluid

Specifications:

- Metal construction
- Pressure balancing volume control with 2-way, two handle diverting
- ➔ Maximum temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- Requires the fluid F1012B or F1022B pressure balancing valve, (sold separately and available with shut off or **sharing in solder, PEX and PEX-W.)

Components:

F1001T	Sleeve tube and cap
FP6016041	Quad Handle
FP801013	Diverter Sleeve
FP605752	Diverter Handle
FP601143-2PB	Square Cover Plate
FP6027008	. 8" Shower Arm
FP20100	5-Function Showerhead
FP6004048	Square Hand Shower
FA104	Slide Bar
FP6001047	. Wall Outlet
FP6001006	. 60" Shower Hose

**sharing available where allowed by code

Kit with Alternate Handle: **F162204T-AS**



Features:



Quad 5-Function Showerhead & Hand Shower Trim Kit

F162204T



Polished Chrome (CP) and Brushed Nickel (BN)

fluid by Sustainable Solutions

F162204T March 2025

fluid

Technical Drawing

Warranty:

3

UPC .

NSE

Certified to NSF/ANSI 61

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

fluid by Sustainable Solutions

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Showerhead & Hand Shower @ 1.5 gpm: **F162204T-15**



