fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6016041	Quad Handle
FP6001033-1PB	Square Cover Plate
FP6000150	6" Square Showerhead
FP6027008	8" Shower Arm
FP6096034	Square Tub Spout

Quad Square Diverting Tub Spout & 6" Shower Trim Kit

F161243T







Features:



Requires non-diverting F1001B or F1021B valve



Integral Stops



Bubble Level

Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)



Slip Fit





F161243T March 2025


fluid


Technical Drawing

F161243T



















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Showerhead @ 1.5 gpm: **F161243T-15**