fluid

Specifications:

- → Metal construction for durability and reliability
- > Pressure balancing, single handle diverting and temperature control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1002B or F1042B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6016041	Quad Handle
FP6001033-2PS	Square Cover Plate
FP10130	4" Square Showerhead
FP6027008	8" Shower Arm
FP6098035L	Curved Tub Spout

Quad Curved Tub Spout & 4" **Shower Trim Kit**

F164110T







Features:



Requires 2-way diverting F1002B or F1042B valve



Integral Stops



Bubble Level




Slip Fit


Polished Chrome (CP), Brushed Nickel (BN) & Matte Black (MB)


fluid


Technical Drawing


F164110T




















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Showerhead @ 1.5 gpm: **F164110T-15**