fluid

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001T	Cartridge Sleeve
FP6028341	Wisdom Handle
FP6001035-1PB	Round Cover Plate
FP900208	8" Switch Shower Arm
FP20100	5-Function Showerhead
FP40120	3-Function Hand Shower*
F933002	18" Switch Slide Bar
FP6001006	60" Shower Hose*

 Matte black uses an FP6001007MB Shower Hose & FP40130MB 3-Function Hand Shower

Features:



Requires non-diverting F1001B or F1021B valve



Integral Stops



Bubble Level

Wisdom 5-Function 18" Switch Shower Trim Kit

F281208T-18





Polished Chrome (CP), Brushed Nickel (BN) and Matte Black (MB)

fluid

Technical Drawing

F281208T-18

















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant

Flow Rate:

Hand Shower & Showerhead 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower & Showerhead @ 1.5 gpm: **F281208T-18-15**