

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1001B or F1021B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001TMB	Sleeve Tube and Cap
FP6028341MB	Wisdom Handle
FP6001035MB-1PB	Round Cover Plate
FP20100MB	5-Function Showerhead
FP6016008MB	8" Shower Arm

Wisdom 5-Function Shower Head Trim Kit

F281006TMB





Features:



Requires non-diverting F1001B or F1021B valve



Integral Stops



Bubble Level


Matte Black (MB)


fluid


Technical Drawing


F281006TMB











Warranty:

NSF Certified to NSF/ANSI 61

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed **ADA Compliant**

Flow Rate:

Showerhead 1.8 gpm @ 60 psig

Low Flow Alternative: Showerhead @ 1.5 gpm: **F281006TMB-15**