fluid

Specifications:

- Stainless Steel Construction
- Designed to replace a standard wall-mounted showerhead and arm with a slide bar system featuring a built-in water outlet and diverter to direct flow to either the showerhead or hand shower
- → Works with the existing rough-in valve—no need to alter plumbing behind the wall or modify the shower wall
- → Two mounting options: drill into shower wall or drill-free using only the supplied waterproof adhesive
- 3-Function Hand Shower
- → Adjustable Slide Bar allows you to change hand shower height
- > 8" Swivelling Switch Shower Arm for adjustable positioning
- Reversible Hose Elbow installs left or right
- → Water Inlet is located at the top installation post
- Built in Check Valve prevents backflow
- Optional 65 mm escutcheons available for larger wall openings (sold separately)

Components:

FP933000	26" Main Slide Bar (Round Trim)
FP900208	8" Shower Arm with 2" Riser
FP40120	3-Function Round Hand Shower *
FP6000350	6" Round Shower Head
FP6001006	60" Shower Hose *

Matte Black Specific Components
FP6001007MB Hose | FP40130MB Hand Shower

Switch Retrofit Shower & Hand Shower Trim Kit

F9308-001



Polished Chrome (CP), Brushed Nickel (BN), and Matte Black (MB)

fluid by **Sustainable Solutions**

Email: help@sustainablesolutions.com


Toll Free: 18004607019


F9308-001 May 2025

WEBSITE

Technical Drawing

F9308-001











Warranty

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Low Flow Alternative: Showerhead and Hand Shower @ 1.5 gpm: **F9308-001-15**

fluid by Sustainable Solutions

Email: help@sustainablesolutions.com

Toll Free: 18004607019

F9308-001 May 2025