# fluid

### fixtures for life

### **Specifications:**

- Stainless Steel Construction
- $\rightarrow$ 3-Function Hand Shower
- ≯ Diverting Tub Spout features slip fit installation
- ≯ Adjustable Slide Bar allows you to change hand shower height
- → 8" Swivelling Switch Shower Arm for adjustable positioning
- Reversible Hose Elbow installs left or right
- Water Inlet is located at the top installation post
- Built in Check Valve prevents backflow ≯
- Requires the fluid F1001B or F1021B pressure balancing valve ≯ (sold separately and available with shut off, PEX and PEX-W)

### **Components:**

F1001T	Sleeve Tube and Cap
FP6001035-1PB	Round Cover Plate
FP6018041	Utopia handle
FP933000	26" Main Slide Bar (Round Trim)
FP900208	8" Shower Arm with 2" Riser
FP40120	3-Function Round Hand Shower
FP6000350	6" Round Shower Head
FP6001006	60" Shower Hose
FP6098034L	Curved Diverting Tub Spout

### Features:




Requires Non-Diverting F1001B or F1021B valve

Integral Stops

ന്ന **Bubble Level** 

> Slip Fit (Tub Spout)

Polished Chrome (CP), and Brushed Nickel (BN)





Email: help@sustainablesolutions.com **Toll Free:** 18004607019

Utopia Switch Tub, Shower & Hand Shower Trim Kit

## F181071T



F181071T May 2025



# fluid

JPC ®

(NSF.)

Certified to NSF/ANSI 61

#### **Technical Drawing**

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

Warranty

2 Year Limited Warranty on all industrial, commercial and business applications.

### **Codes and Standards:**

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

8<sup>15</sup>/16" [227.4m m

4<sup>11</sup>/16

[172.8m m

### **Flow Rate:**

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig Low Flow Alternative: Showerhead and Hand Shower @ 1.5 gpm: F181071T-15

#### F181071T May 2025

WEBSITE





1/2"-14N PT

### F181071T



