fluid

fixtures for life

Quad Switch Shower & Hand

Shower Trim Kit

F161070T

Specifications:

- Stainless Steel Construction
- 3-Function Hand Shower
- 5-Function Shower Head
- Diverting Tub Spout features slip fit installation
- Adjustable Slide Bar allows you to change hand shower height
- 8" Swivelling Switch Shower Arm for adjustable positioning
- Reversible Hose Elbow installs left or right
- → Water Inlet is located at the top installation post
- Built in Check Valve prevents backflow
- Requires the fluid F1001B or F1021B pressure balancing valve (sold separately and available with shut off, PEX and PEX-W)

Components:

F1001T	Sleeve Tube and Cap
FP6001033-1PB	Square Cover Plate
FP6016041	Quad Handle
FP933000	26" Main Slide Bar (Round Trim)
FP900208	8" Shower Arm with 2" Riser
FP40120	3-Function Round Hand Shower
FP20100	5-Function Showerhead
FP6001006	60" Shower Hose
FP6097034	Square Diverting Tub Spout

Features:



Requires Non-Diverting F1001B or F1021B valve

Integral Stops Speed Connect (Slide Bar) Bubble Level

Slip Fit (Tub Spout) Polished Chrome (CP), and Brushed Nickel (BN)





F161070T May 2025

Email: help@sustainablesolutions.com **Toll Free:** 1 800 460 7019

fluid by Sustainable Solutions



fluid



F161070T

Dg.Z

10¹/₈" [257.5mm] O.D.1" O.D.3¹⁵/16 4¹¹/16" [119.3mm] O.D.1" [25mm] 0.D.1¹⁵ £ 4-(1/2"-14NPT) 2¹/4"-3¹/16" [57mm-77mi 1⁷/8" 4⁷/8" 5¹/₈" [130mm] 1145 2¹/2" [64mm] 1¹³/16" 5½ 130,2

Warranty

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig Low Flow Alternative: Showerhead and Hand Shower @ 1.5 gpm: F161070T-15

F161070T May 2025

Email: help@sustainablesolutions.com **Toll Free:** 18004607019

fluid by Sustainable Solutions

WEBSITE

