fluid

fixtures for life

Specifications:

- Stainless Steel Construction →
- 5-Function Shower Head
- **3-Function Hand Shower** \rightarrow
- Adjustable Slide Bar allows you to change hand shower height →
- → Diverting Tub Spout features slip fit installation
- \rightarrow 8" Swivelling Switch Shower Arm for adjustable positioning
- → Reversible Hose Elbow installs left or right
- → Water Inlet is located at the top installation post
- **>** Built in Check Valve prevents backflow
- ≯ Requires the fluid F1001B or F1021B pressure balancing valve (sold separately and available with shut off, PEX and PEX-W)

Components:

F1001T	Sleeve Tube and Cap
FP6001035-1PB	Round Cover Plate
FP6028341	Wisdom Handle
FP933000	26" Main Slide Bar (Round Trim)
FP900208	8" Shower Arm with 2" Riser
FP40120	3-Function Round Hand Shower *
FP20100	5-Function Showerhead
FP6001006	60" Shower Hose *
FP6098034L	Curved Diverting Tub Spout

Features:



Requires Non-Diverting F1001B or F1021B valve

Integral Stops Speed Connect (Slide Bar)



Slip Fit (Tub Spout) Matte Black Specific Components FP6001007MB Hose | FP40130MB Hand Shower

Polished Chrome (CP), Brushed Nickel (BN), and Matte Black (MB)



Toll Free: 18004607019

Wisdom Switch Tub, Shower & Hand Shower Trim Kit

F281070T





fluid



F281070T



Warranty

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

1/2″-14N PT

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed

10³/₁₆" [258.4m m

2¹/₄"-3¹/₁₆" [57mm-77mm

> 4⁹/₁₆" [115.1m m

> > - 6¹³/₁₆" [172.8m m

504



Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig Low Flow Alternative: Showerhead and Hand Shower @ 1.5 gpm: **F281070T-15**

F281070T May 2025

fluid by **Sustainable Solutions** Email: help@sustainablesolutions.com Toll Free: 18004607019



