

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control with 2-way single handle diverting
- → Maximum temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1002B or F1042B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W, F1960 Expansion PEX.)

Components:

F1001T	Cartridge Sleeve
FP6019441	Yaletown Handle
FP6001035-2PS	Round Cover Plate
FP6000350	6" Showerhead
FP6016008	8" Shower Arm
FP6001048	Round Hand Shower
FP6001010	Hand Shower Holder
FP6082048	Wall Outlet
FP6001006	60" Shower Hose

Features:



Requires 2-way diverting F1002B or F1042B valve



Integral Stops



Bubble Level

Yaletown 6" Shower & Hand **Shower Trim Kit**

F194101T



Polished Chrome (CP) and Brushed Nickel (BN)

fluid by Sustainable Solutions

Email: help@sustainablesolutions.com


Toll free: 1 800 460 7019



fluid

Technical Drawing

F194101T



Warranty:

NSF

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Shower-head & Hand Shower @ 1.5 gpm: **F194101T-15**

fluid by Sustainable Solutions

Email: help@sustainablesolutions.com

Toll free: 18004607019



F194101T June 2025