

Specifications:

- ➔ Metal construction
- ➔ Pressure balancing volume control with 2-way diverter
- ➔ Maximum temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- ➔ Requires the fluid F1012B or F1022B pressure balancing valve, (sold separately and available with shut off or **sharing in solder, PEX and PEX-W.)

Components:

F1001TMB	Sleeve Tube and Cap
FP801013MB	Diverter Sleeve
FP601143MB-2PB	Square Cover Plate
FP605752MB	Square Diverter Handle
FP6016041MB	Quad Handle
FP6027008MB	8" Shower Arm
FP20100MB	5-Function Showerhead
FP6056034MB	Cubed Tub Spout

**sharing available where allowed by code

Kit with Alternate Handle: **F162212TMB-AS**



Features:

 Requires 2-way diverting F1012B or F1022B valve

 Integral Stops

 Bubble Level

 Speed Connect

Quad Tub & 5-Function Shower Trim Kit


F162212TMB



Matte Black (MB)

Technical Drawing

F162212TMB



Warranty:

Limited Lifetime Faucet Warranty
against material and manufacturing
defects for residential use.

2 Year Limited Warranty on all industrial,
commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1

CSA B125.1

IAPMO / cUPC Listed

ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig

Hand Shower 1.8 gpm @ 60 psig

Low Flow Alternative: Hand Shower
@ 1.5 gpm: **F162212TMB-15**