fluid

Specifications

- > Under mount single bowl tight radius kitchen sink
- → High quality fluid sink is formed of #18 gauge (1.0 mm) type 304 stainless steel
- Minimum cabinet size: 24" (609mm)
- → Has 3 ½" (90mm) diameter recessed drain opening, positioned at the rear of the sink
- → Full undercoating and large rubber pads for noise reduction and condensation elimination.
- Cut-out template and mounting hardware are included.
- Stainless steel basket strainer is available and sold separately.
- → The sink is stack packed in bulk.

Overall dimensions:

20"(508 mm) x 18"(457mm) x 9"(229mm)

Codes and Standards

- ANSI/ASME A112.19.3-2000
- CSA B45 Series-02
- → IAPMO / cUPC Listed


Warranty



Limited Lifetime Sink Warranty against material and manufacturing defects for residential use.

 $1\,\mbox{Year}$ Limited Warranty on all industrial, commercial and business applications.

Installation Details




Optional Accesories

Such as colander, bottom grid and cutting board may be available. Please contact our sales representative for details.

fluid Tight Radius Undermount Single Bowl Kitchen Sink

FSN-USR2018





Finish Available: Stainless Steel

Important Note:

Cut-out template is included in the carton box. Fabricator must check it for accuracy. We are not responsible for wrong cutting.