fluid[™]

Specifications:

- → Metal construction for durability and reliability
- → Pressure balancing volume control with 3-way, two handle diverting
- → Max-temperature limit stop for added safety
- → Integral stop check valves for easy maintenance
- → Requires the fluid F1003B or F1023B pressure balancing valve, (sold separately and available with shut off or **sharing in solder, PEX and PEX-W.)

Components:

F1001T	Sleeve tube and cap
FP6018041	Utopia Handle
FP801013	Diverter Sleeve
FP605752	Diverter Handle
FP6001142-3PB	Round Cover Plate
FP6002150	8" Round Rain Showerhead
FP40120	3-Function Hand Shower
FA802	Slide Bar With Integral Outlet
FP6001006	60" Shower Hose
FP6031034	Utopia Tub Spout

**sharing available where allowed by code

Kit with Alternate Handle: **F183024T-ABS-AR**





Features:



Requires 3-way diverting F1003B or F1023B valve



Integral Stops



Bubble Level



Speed Connect

Utopia Tub, 3-Function Hand Shower and 8" Rain Shower Kit

F183024T-ABS





Polished Chrome (CP) and Brushed Nickel (BN)



Technical Drawing

F183024T-ABS



















Warranty:

Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.

2 Year Limited Warranty on all industrial, commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1 CSA B125.1 IAPMO / cUPC Listed EPA Watersense Listed ADA Compliant

Flow Rate:

Showerhead 1.8 gpm @ 60 psig Hand Shower 1.8 gpm @ 60 psig Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Hand Shower & @ 1.5 gpm: **F183024T-ABS-15**