

Specifications:

- ➔ Metal construction for durability and reliability
- ➔ Pressure balancing volume control
- ➔ Max-temperature limit stop for added safety
- ➔ Integral stop check valves for easy maintenance
- ➔ 6" round shower head and 8" shower arm
- ➔ Round diverting tub spout with slip fit connection
- ➔ Valve and trim packages are sold separately
- ➔ Requires the fluid F1001B pressure balancing valve, (sold separately and available in solder, PEX and PEX-W.)

Components:

F1001TBG	Sleeve Tube and Cap
FP6024041BG	Citi Handle
FP6001035BG-1PB.....	Round Cover Plate
FP6055034BG.....	7.5" Round Diverting Tub Spout
FP6016008BG.....	8" Shower Arm
FP6000350BG.....	6" Round Shower Head

Citi Round Diverting Tub Spout & 6" Shower Head Trim Kit

F241038TBG







**Features:**

- | | |
|---|---|
|  Requires F1001B |  Bubble Level |
|  Integral Stops |  Slip Fit Connection |

Brushed Gold (BG)

Technical Drawing

F241038TBG



Warranty:

Limited Lifetime Faucet Warranty
against material and manufacturing
defects for residential use.

2 Year Limited Warranty on all industrial,
commercial and business applications.

Codes and Standards:

ANSI/ASME A112.18.1

CSA B125.1

IAPMO / cUPC Listed

EPA Watersense Listed

Flow Rate:

Shower Head 1.8 gpm @ 60 psig

Tub Spout 4.5 gpm @ 60 psig

Low Flow Alternative: Shower Head
@ 1.5 gpm: **F241038TBG-15**